

I. PRODUCT IDENTIFICATION					
Chemical Trade Name (as used on label): Industrial Nickel Cadmium Storage Battery w/ Pocket Plate (VARTA T, TP and TSP range)			Chemical Family/Classification: N/A		
Manufacturer's Name/Address: EnerSys P.O. Box 14145 2366 Bernville Road Reading, PA 19612-4145			Telephone: For information and emergencies, contact EnerSys' Environmental, Health & Safety Dept. at 610-208-1996 24-Hour Emergency Response Contact: CHEMTREC DOMESTIC: 800-424-9300 CHEMTREC INTERNATIONAL: 703-527-3877		
II. HAZARDOUS INGREDIENTS/IDENTIFY INFORMATION					
Components	CAS Number	Approximate % by Wt. Or Vol.	Air Exposure Limits (ug/m ³)		
			OSHA	ACGIH	NIOSH
Nickel (As Nickel and Nickel hydroxide)	7440-02-0 1205-44-87	9-10	1.0	0.1	0.015
Cadmium (As Cadmium And Cadmium Hydroxide)	7440-43-9 21041-95-2	8-10	0.005	0.01	N/A
Iron (Fe)	7439-89-6	20-25	10.0	5.0	5.0
Stainless Steel (Fe, Ni, Cr)	N/A	7-15	N/A	N/A	N/A
Cobalt (as Cobalt hydroxide)	7440-48-4	0	0.1	0.02	0.05
Potassium hydroxide Solution (KOH)	1310-58-3	30-40	N/A	N/A	2.0
Lithium Hydroxide Solution (LiOH)	1310-66-3	<1	N/A	N/A	N/A
III. PHYSICAL DATA					
Electrolyte:					
Boiling Point:	N/A	Specific Gravity (H₂O = 1):	1.2 kg/l		
Melting Point:	N/A	Vapor Pressure (mm Hg):			
Solubility in Water:	100%	Vapor Density (AIR = 1):			
Evaporation Rate: (Butyl Acetate = 1)		% Volatile by Weight:			
Appearance and Odor:	Manufactured article; no apparent odor. Electrolyte is a clear liquid with a sharp, penetrating, pungent odor.				
IV. FIRE AND EXPLOSION HAZARD DATA					
Flash Point: N/A	Flammable Limits: LEL = N/A		UEL = N/A		
Extinguishing Media: Dry chemical, CO ₂ , water spray, or alcohol-resistant foam.					
Special Fire Fighting Procedures: Use full body protective clothing and full face piece. Self-contained breather apparatus in a positive pressure mode. Molted and overheated Cd and Ni produce fume, vapor or dust. Under these conditions, Ni or Cd is suspected carcinogen. KOH is highly caustic. Contact with eye and skin must be avoided. No heating or smoking during handling or inspection. Do not cause sparks.					
V. REACTIVITY DATA					
Stability: Stable					
Conditions To Avoid: Avoid shorting batteries such as contacting across terminals with any metal object. Avoid continuous temperatures over 190 degrees F.					
Incompatibility: (Materials to avoid) Do not fill cells with Lead Acid Battery electrolyte (Sulfuric Acid).					
Hazardous Decomposition Products: Nickel compounds, Cadmium compounds, and caustic liquid.					
VI. HEALTH HAZARD DATA					
Inhalation: Fumes irritate nose and throat but fumes generated only if batteries are on charge (not a transportation condition).					
Ingestion: Severe irritation of internal tissues. Contact physician immediately.					
Skin Contact: Sever irritation and inflammation. Flush with water. Obtain medical attention.					
Skin Absorption: Severe irritation and inflammation. Flush with water. Obtain medical attention.					
Eye Contact: Severe irritation. Possible corneal damage. Flush with water for 15 minutes.					

EMERGENCY AND FIRST AID PROCEDURES:																																		
Inhalation:	Not applicable to batteries in transit but if on charge in confined, poorly ventilated area and fumes irritating, remove person to fresh air.																																	
Ingestion:	Get medical help. Give patient copious amounts of water. Do not induce vomiting.																																	
Skin:	Remove contaminated clothing and flush skin with water for 15 minutes. Do not attempted to neutralize with alkaline.																																	
Eyes:	Hold eyelids open and flush with clean water for 15 minutes. Get medical help promptly.																																	
VII. PRECAUTIONS FOR SAFE HANDLING AND USE																																		
Spill or Leak Procedures:	Clean up personnel should wear safety goggles, rubber gloves, rubber boots and rubber apron. Use weak acids, ex: boric acid, acetic acid.																																	
Waste Disposal Methods:	Consult waste disposal business for proper disposition. Do not empty in common sewer systems.																																	
Handling and Storage:	Rubber boots and rubber aprons, chemical goggles or full-face shield should be worn while handling. Cells/Batteries to be stored in standard battery room conditions.																																	
VIII. CONTROL MEASURES																																		
Personal Protective Equipment:	Rubber gloves, safety goggles, alkaline resistant protective clothing.																																	
IX. OTHER REGULATORY INFORMATION																																		
U.S. DOT:	<p><u>The shipping information is as follows:</u></p> <table border="0"> <tr> <td>Proper Shipping Name: Batteries, wet, filled with alkali</td> <td>Packing Group: III</td> </tr> <tr> <td>Hazardous Class: 8</td> <td>Label/Placard Required: Corrosive</td> </tr> <tr> <td>UN Identification: UN2795</td> <td></td> </tr> </table> <p>Reference 49 CFR packing instructions 173.159 and 173.159a</p>	Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: III	Hazardous Class: 8	Label/Placard Required: Corrosive	UN Identification: UN2795																												
Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: III																																	
Hazardous Class: 8	Label/Placard Required: Corrosive																																	
UN Identification: UN2795																																		
IATA:	<p><u>The shipping information is as follows:</u></p> <table border="0"> <tr> <td>Proper Shipping Name: Batteries, wet, filled with alkali</td> <td>Packing Group: II</td> </tr> <tr> <td>Hazardous Class: 8</td> <td>Label/Placard Required: Corrosive</td> </tr> <tr> <td>UN Identification: UN2795</td> <td></td> </tr> </table> <p>Reference IATA packing instructions 870</p>	Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: II	Hazardous Class: 8	Label/Placard Required: Corrosive	UN Identification: UN2795																												
Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: II																																	
Hazardous Class: 8	Label/Placard Required: Corrosive																																	
UN Identification: UN2795																																		
IMDG:	<p><u>The shipping information is as follows:</u></p> <table border="0"> <tr> <td>Proper Shipping Name: Batteries, wet, filled with alkali</td> <td>Packing Group: N/A</td> </tr> <tr> <td>Hazardous Class: 8</td> <td>Label/Placard Required: Corrosive</td> </tr> <tr> <td>UN Identification: UN 2795</td> <td></td> </tr> </table> <p>Reference IMDG packing instructions P801</p>	Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: N/A	Hazardous Class: 8	Label/Placard Required: Corrosive	UN Identification: UN 2795																												
Proper Shipping Name: Batteries, wet, filled with alkali	Packing Group: N/A																																	
Hazardous Class: 8	Label/Placard Required: Corrosive																																	
UN Identification: UN 2795																																		
RCRA:	Spent nickel-cadmium batteries are regulated as universal waste by the EPA when recycled, however state and international regulations may vary.																																	
CERCLA (Superfund) and EPCRA:	<p>(a) EPCRA Section 312 Tier 2 reporting is required for batteries if potassium hydroxide, nickel and/or cadmium is present in quantities of 10,000 lbs. or more.</p> <p>(b) <u>Supplier Notification:</u> This product contains toxic chemicals, which may be reportable under EPCRA Section 313 Toxic Chemical Release Inventory (Form R) requirements. If you are a manufacturing facility under SIC codes 20 through 39, the following information is provided to enable you to complete the required reports:</p> <table border="0"> <thead> <tr> <th style="text-align: left;"><u>Toxic Chemical</u></th> <th style="text-align: left;"><u>CAS Number</u></th> <th style="text-align: left;"><u>Approximate % by Wt.</u></th> </tr> </thead> <tbody> <tr> <td>Nickel</td> <td>744-02-0</td> <td>9-10</td> </tr> <tr> <td>Cadmium</td> <td>7440-43-9</td> <td>8-10</td> </tr> <tr> <td>Cobalt</td> <td>7440-48-4</td> <td>0.2</td> </tr> </tbody> </table> <p>If you distribute this product to other manufacturers in SIC Codes 20 through 39, this information must be provided with the first shipment of each calendar year.</p> <p>The Section 313 supplier notification requirement does not apply to batteries, which are "consumer products".</p> <p>(c) <u>TSCA:</u> Ingredients in EnerSys' batteries are listed in the TSCA Registry as follows:</p> <table border="0"> <thead> <tr> <th style="text-align: left;"><u>Components</u></th> <th style="text-align: left;"><u>CAS Number</u></th> <th style="text-align: left;"><u>TSCA Status</u></th> </tr> </thead> <tbody> <tr> <td>Nickel</td> <td>7440-02-0</td> <td>Listed</td> </tr> <tr> <td>Cadmium</td> <td>7440-43-9</td> <td>Listed</td> </tr> <tr> <td>Iron</td> <td>7439-89-6</td> <td>Listed</td> </tr> <tr> <td>Potassium Hydroxide</td> <td>1310-58-3</td> <td>Listed</td> </tr> <tr> <td>Cadmium Hydroxide</td> <td>21041-95-2</td> <td>Listed</td> </tr> <tr> <td>Cobalt</td> <td>7440-48-4</td> <td>Listed</td> </tr> </tbody> </table>	<u>Toxic Chemical</u>	<u>CAS Number</u>	<u>Approximate % by Wt.</u>	Nickel	744-02-0	9-10	Cadmium	7440-43-9	8-10	Cobalt	7440-48-4	0.2	<u>Components</u>	<u>CAS Number</u>	<u>TSCA Status</u>	Nickel	7440-02-0	Listed	Cadmium	7440-43-9	Listed	Iron	7439-89-6	Listed	Potassium Hydroxide	1310-58-3	Listed	Cadmium Hydroxide	21041-95-2	Listed	Cobalt	7440-48-4	Listed
<u>Toxic Chemical</u>	<u>CAS Number</u>	<u>Approximate % by Wt.</u>																																
Nickel	744-02-0	9-10																																
Cadmium	7440-43-9	8-10																																
Cobalt	7440-48-4	0.2																																
<u>Components</u>	<u>CAS Number</u>	<u>TSCA Status</u>																																
Nickel	7440-02-0	Listed																																
Cadmium	7440-43-9	Listed																																
Iron	7439-89-6	Listed																																
Potassium Hydroxide	1310-58-3	Listed																																
Cadmium Hydroxide	21041-95-2	Listed																																
Cobalt	7440-48-4	Listed																																
CAA:	EnerSys supports preventative actions concerning ozone depletion in the atmosphere due to emissions of CFC's and other ozone depleting chemicals (ODC's), defined by the USEPA as Class I substances. Pursuant to Section 611 of the Clean Air Act Amendments (CAAA) of 1990, finalized on January 19, 1993, EnerSys established a policy to eliminate the use of Class I ODC's prior to the May 15, 1993 deadline.																																	